

VULCASEAL[®]

AF300



VULCASEAL AF300 IS A CURATIVE TREATMENT PROVIDING LONG-LASTING PROTECTION AGAINST AND RADICAL DESTRUCTION OF MOSS, LICHEN, ALGAE AND FUNGI.

PRODUCT DESCRIPTION

Vulcaseal AF300 is preventative: the active matter is fixed into the substrate, stopping the proliferation of mould and making the germination of parasitic plants impossible.

Vulcaseal AF300 is curative: destroys all the parasitic vegetation which is then eliminated by rain or by simple brushing.

Vulcaseal AF300 does not change the colour of the substrate, is not a film-former and does not turn yellow. Replaces the common acidic or alkaline detergents, which are always harmful to substrates. Inoffensive towards the substrates.

Vulcaseal AF300 is recommended to treat walls, roofs, balconies, fountains, basins, monuments, fences, terraces, patio blocks, boat hulls, awning blinds and tennis courts.

Vulcaseal AF300 has residual effects for 2 to 3 years after application (depending on the exposure).

CHEMICAL COMPOSITION

Vulcaseal AF300 is formulated with quaternary ammonium compounds. Non-ionic surface-active agent.

CHARACTERISTICS

Colourless, so does not alter the aesthetics or nature of the substrate

Non-flammable

Not dangerous

Easy to use

Strong ability to penetrate

Product in aqueous phase

Contains no acid, chlorine or nonylphenol

Residual effects

Can be used inside and outside

VULCASEAL[®]

AF300



CORROSIVE

Vulcaseal AF300 is formulated with quaternary ammonium compounds. Non-ionic surface-active agent.



PACKAGING

1 and 5 litre containers.

TECHNICAL DATA

Physical State at 20 °C	Liquid
Appearance	Greenish
Odour	Citronella
pH	8 ± 0.5
Density	1.0 Kg/L
Solubility in water [vol/vol]	Fully soluble
Flash Point	N/A

COVERAGE PER LITRE

The figures indicated are approximate and should be used only as a general guideline: **1 Litre = 8 to 12m²**.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area and ideally at 20-25°C.

CLEANING EQUIPMENT

Clean tools and equipment immediately after use with water.

APPLICATION

Vulcaseal AF300 is ready to use but can be diluted up to 1: 2 with water.

Always carry out a test first to ensure the finished result is acceptable.

Apply in dry weather on a dry or slightly wet substrate, by spraying until the surface is saturated.

If the substrate is badly infected, try brushing it down before application.

Allow to act for 10 to 15 days. Be careful, as if applying in cold weather (less than 10 °C), the de-mossing will take longer.

Eliminate the residue by brushing or by just letting the weather take care of it naturally.

If it rains in the 48 hours following the treatment, it must be repeated.

Important: The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use in individual cases.

For more information, please see the Material Safety Data Sheet.

RECOMMENDATIONS

To obtain the best look and results on application, Vulcaseal AF300 should be shaken before use and must only be used when the temperature of the surfaces to be treated is greater than 5°C.

Take care not to spray onto the surrounding vegetation.

Do not apply during rain, frost, or when surface and air temp is <5°C and >30°C.

Do not dilute or mix with another product.

HEALTH AND SAFETY

Hand Protection Wear protective gloves.

Skin Protection Not required.

Respiratory Protection Under normal conditions of use where there is adequate ventilation, no special respiratory protection equipment is needed.

Eye Protection If there is a real risk of splashing, wear protective goggles.

In case of ingestion Do not provoke vomiting. Contact a doctor or a specialist.

Keep out of the reach of children.