

VULCASEAL®

V286



WATER AND OIL REPELLENT TOTAL PROTECTION FOR ALL POROUS FLOORS SUBJECT TO HEAVY TRAFFIC. INTERIOR / EXTERIOR ANTI-STAIN TREATMENT FOR GRANITE, MARBLE, SANDSTONE AND SLATE.

PRODUCT DESCRIPTION

Vulcaseal V286 has all the water-repellent, oil-repellent and anti-soiling properties needed to protect porous building substrates in a single application. Acts against the main causes of degradation, such as atmospheric and industrial pollution, greasy soiling, water seepage, acid rain and chewing gum.

Vulcaseal V286 is ideal for treating all porous materials: natural stone, synthetic stone, terracotta, architectural concrete, interlocking paving blocks, cement, etc. Especially recommended for the protection of substrates subject to heavy traffic: pavements, pedestrian zones, parking zones, terraces and lobbies etc.

Vulcaseal V286 is a non film-forming impregnating treatment, meaning that the treated surface remains permeable to air and water vapour.

Vulcaseal V286 is an environmentally friendly product, completely waterborne (non-toxic, solvent and silicone free). The product delays a material's ageing process and provides protection against graffiti.

CHEMICAL COMPOSITION

Vulcaseal V286 is a non-hazardous, waterborne fluorinated co-polymer based solution.

CHARACTERISTICS

Protection against water, frost, oil and dirt

Abrasion and scratch resistant

Anti-staining, anti-dirt

Colourless, so does not alter the aesthetics or nature of the substrate

Prevents the penetration of water and oily liquids

UV resistant, does not discolour

Invisible once dry

95% + biodegradable according to OECD standards

For further information or technical advice call 020 8778 9000

Vulcaseal is a Trimline product ©Trimline 2011

www.vulcaseal.co.uk

Issue VS DS 08.11

VULCASEAL®

V286



PACKAGING

1, 5 and 25 litre containers.

TECHNICAL DATA

| | |
|-------------------------------|---------------|
| Physical State at 20 °C | Liquid |
| Appearance | Colourless |
| Odour | None |
| pH | 8 ± 0.5 |
| VOC | <1 g/l |
| Boiling Point | 100 °C |
| Density | 1.0 Kg/L |
| Solubility in water [vol/vol] | Fully soluble |
| Flash Point | N/A |

COVERAGE PER LITRE

Coverage depends on the porosity of the material. The figures indicated are approximate and should be used only as a general guideline: **1 Litre = 5 to 10m²**.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area and ideally at 20-25°C.

CLEANING EQUIPMENT

Clean tools and equipment immediately after use with water.

APPLICATION

Shake the container well before use.

Use directly from the container, do not dilute or mix with another product.

Always carry out a test first to ensure the finished result is acceptable.

Ensure the surface to be treated is clean, dust-free and dry before applying Vulcaseal V286.

Apply using a low-pressure sprayer, roller or brush.

Substrate must be impregnated until saturation, either in one application or in two "wet-on-wet" applications.

On vertical surfaces, apply from the bottom up.

Drying time 24 hours.

For the best results wait 5 to 7 days.

Important: The contents of this document are the result of our experience with this product. We cannot be in any way held liable for its use in individual cases.

For more information, please see the Material Safety Data Sheet.

RECOMMENDATIONS

Remove all atmospheric pollution-related dirt from all surfaces to be treated before starting the treatment.

To obtain the best look and results on application, Vulcaseal V286 should be shaken before use and must only be used when the temperature of the surfaces to be treated is above 5°C.

Do not apply during rain, frost, or when surface and air temp is <10°C and >30°C.

Do not dilute or mix with another product.

HEALTH AND SAFETY

Hand Protection Wear domestic gloves.

Skin Protection Not required.

Respiratory Protection Under normal conditions of use where there is adequate ventilation, no special respiratory protection equipment is needed.

Eye Protection Wear safety goggles.

In case of ingestion Do not provoke vomiting. Contact a doctor or a specialist.

Keep out of the reach of children.